


Small Surface Mount Ultra Fast Recovery Rectifiers
Reverse Voltage 100 to 800 Volts, Forward Current 1.0 Ampere
Features


- For surface mounted applications
- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High temperature soldering : 260°C / 10 seconds at terminals
- Lead free in comply with EU RoHS 2002/95/EC directives.
- Green molding compound as per IEC61249 Std..(Halogen Free)

Mechanical Data


- Case : JEDEC SOD-123FL, Molded plastic
- Terminals : Solderable per MIL-STD-750, Method 2026
- Polarity : Color band denotes cathode end
- Weight : 0.015 gram (Approx.)

Marking


SOD-123FL



DIM	Unit :mm		Unit:inch	
	MIN	MAX	MIN	MAX
A	0.8	1.2	0.031	0.047
A1	0	0.1	0.000	0.004
B	0.6	1.05	0.024	0.041
C	0.05	0.25	0.002	0.010
D	1.55	2	0.061	0.079
E	2.5	3.1	0.098	0.122
L	0.43	1.1	0.017	0.043
HE	3.5	3.9	0.138	0.154



Maximum Ratings & Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified
 Single phase half wave 60 HZ, resistive or inductive load
 For capacitive load, derate current by 20%

Parameter	Symbol	US 1001FL	US 1002FL	US 1004FL	US 1006FL	US 1008FL	Unit	Remark	
Marking Code		U1B	U1D	U1G	U1J	U1K			
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	100	200	400	600	800	V		
Maximum RMS Voltage	V_{RMS}	70	140	280	420	560	V		
Maximum DC Blocking Voltage	V_{DC}	100	200	400	600	800	V		
Maximum Average Forward Rectified Current	$I_F(AV)$	1.0						A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	30						A	
Maximum Instantaneous Forward Voltage	V_F	1.0		1.4		1.7	V	$I_F=1A$	
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	10						uA	$T_a=25^\circ C$
		50						uA	$T_a=125^\circ C$
Typical Junction Capacitance	C_J	9.0						pF	Note 1
Reverse Recovery Time	t_{rr}	50			100			ns	Note 2
Typical Thermal Resistance	$R_{th(j-a)}$	180						°C /W	Note 3
Operation Junction Temperature Range	T_J	-55 to +150						°C	
Storage Temperature Range	T_{STG}	-55 to +150						°C	

Note 1. Measured at 1MHz and Applied Reverse Voltage of 4.0Volts D.C.

Note 2. Reverse Recovery Test Conditions : $I_F=0.5A$, $I_R=1.0A$, $I_{RR}=0.25A$

Note 3. Thermal resistance from junction to ambient.



Ratings and Characteristics Curves ($T_a=25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance




Fig.5 Typical Reverse Characteristics

