


Peak Pulse Power 600W Breakdown Voltage 6.8 to 550V
Features

- Plastic package has underwriters laboratory flammability Classification 94V-0
- Low profile package with built-in strain relief for surface mounted applications
- 600W surge capability at 10×100us waveform, duty cycle : 0.01%
- Excellent clamping capability
- Low zener impedance
- Very Fast response time
- High temperature soldering guaranteed : 250°C/10 seconds at terminals

Mechanical Data

- Case : Molded plastic
- Lead : Axial leads, solderable per MIL-STD-750, Method 2026
- Polarity : Color band denotes cathode except bipolar
- Weight : approx. 0.093grams


Devices for Bidirectional Applications

For bi-directional devices, use suffix CA (e.g. P6SMB10CA). Electrical characteristics apply in both directions.

Maximum Ratings and Thermal Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	Rated Value	Unit	Remark
Peak Pulse Power Dissipation with a 10/1000us Waveform	P _{PPM}	Minimum 600	W	Note 1, 2
Peak Pulse Current with a 10/1000us Waveform	I _{PPM}	See Next Table	A	Note 1
Power dissipation on infinite heatsink, T _A =50°C	P _{M(AV)}	5.0	W	Note 2
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Uni-directional only	I _{FSM}	100	A	Note 2
Maximum Instantaneous Forward Voltage at 50A for Uni-directional Only	V _F	3.5	V	
Thermal Resistance Junction to Leads	R _{th(j-l)}	20	°C/W	
Thermal Resistance Junction to Ambient air	R _{th(j-a)}	100	°C/W	Note 3
Operating and Storage Temperature Range	T _J , T _{STG}	-55 to +150	°C	

Note 1. Non-repetitive current pulse per Fig.3 and derated above Ta=25°C per Fig.2.

Note 2. Mounted on 0.2 × 0.2" (5.0×5.0mm) copper pad to each terminal

Note 3. Mounted on minimum recommended pad layout



Electrical Characteristics (Ta=25°C unless otherwise noted)

Device	Device Marking Code		Breakdown Voltage(Note 1) V _{BR} (V)		Test Current @I _T (mA)	Stand-Off Voltage V _{WM} (V)	Maximum Reverse Leakage at V _{WM} I _D (uA)	Maximum Peak Pulse Current I _{PPM} (Note 2) (A)	Maximum Clamping Voltage at I _{PPM} V _C (V)	Maximum Temperature Coefficient of V _{BR} (%/°C)
	Uni	Bi	Min	Max						
P6SMB6.8A	6V8A	6V8C	6.45	7.14	10	5.80	1000	57.1	10.5	0.057
P6SMB7.5A	7V5A	7V5C	7.13	7.88	10	6.40	500	53.1	11.3	0.061
P6SMB8.2A	8V2A	8V2C	7.79	8.61	10	7.02	200	49.6	12.1	0.065
P6SMB9.1A	9V1A	9V1C	8.65	9.55	1.0	7.78	50	44.8	13.4	0.068
P6SMB10A	10A	10C	9.50	10.5	1.0	8.55	10	41.4	14.5	0.073
P6SMB11A	11A	11C	10.5	11.6	1.0	9.40	5.0	38.5	15.6	0.075
P6SMB12A	12A	12C	11.4	12.6	1.0	10.2	5.0	35.9	16.7	0.078
P6SMB13A	13A	13C	12.4	13.7	1.0	11.1	5.0	33.0	18.2	0.081
P6SMB15A	15A	15C	14.3	15.8	1.0	12.8	1.0	28.3	21.2	0.084
P6SMB16A	16A	16C	15.2	16.8	1.0	13.6	1.0	26.7	22.5	0.086
P6SMB18A	18A	18C	17.1	18.9	1.0	15.3	1.0	23.8	25.2	0.088
P6SMB20A	20A	20C	19.0	21.0	1.0	17.1	1.0	21.7	27.7	0.090
P6SMB22A	22A	22C	20.9	23.1	1.0	18.8	1.0	19.6	30.6	0.092
P6SMB24A	24A	24C	22.8	25.2	1.0	20.5	1.0	18.1	33.2	0.094
P6SMB27A	27A	27C	25.7	28.4	1.0	23.1	1.0	16	37.5	0.096
P6SMB30A	30A	30C	28.5	31.5	1.0	25.6	1.0	14.5	41.4	0.097
P6SMB33A	33A	33C	31.4	34.7	1.0	28.2	1.0	13.1	45.7	0.098
P6SMB36A	36A	36C	34.2	37.8	1.0	30.8	1.0	12.0	49.9	0.099
P6SMB39A	39A	39C	37.1	41.0	1.0	33.3	1.0	11.1	53.9	0.100
P6SMB43A	43A	43C	40.9	45.2	1.0	36.8	1.0	10.1	59.3	0.101
P6SMB47A	47A	47C	44.7	49.4	1.0	40.2	1.0	9.3	64.8	0.101
P6SMB51A	51A	51C	48.5	53.6	1.0	43.6	1.0	8.6	70.1	0.102
P6SMB56A	56A	56C	53.2	58.8	1.0	47.8	1.0	7.8	77.0	0.103
P6SMB62A	62A	62C	58.9	65.1	1.0	53.0	1.0	7.1	85.0	0.104
P6SMB68A	68A	68C	64.6	71.4	1.0	58.1	1.0	6.5	92.0	0.104
P6SMB75A	75A	75C	71.3	78.8	1.0	64.1	1.0	5.8	103	0.105
P6SMB82A	82A	82C	77.9	86.1	1.0	70.1	1.0	5.3	113	0.105
P6SMB91A	91A	91C	86.5	95.5	1.0	77.8	1.0	4.8	125	0.106
P6SMB100A	100A	100C	95.0	105	1.0	85.5	1.0	4.4	137	0.106
P6SMB110A	110A	110C	105	116	1.0	94.0	1.0	3.9	152	0.107
P6SMB120A	120A	120C	114	126	1.0	102	1.0	3.6	165	0.107
P6SMB130A	130A	130C	124	137	1.0	111	1.0	3.4	179	0.107
P6SMB150A	150A	150C	143	158	1.0	128	1.0	2.9	207	0.108
P6SMB160A	160A	160C	152	168	1.0	136	1.0	2.7	219	0.108
P6SMB170A	170A	170C	162	179	1.0	145	1.0	2.6	234	0.108
P6SMB180A	180A	180C	171	189	1.0	154	1.0	2.4	246	0.108
P6SMB200A	200A	200C	190	210	1.0	171	1.0	2.2	274	0.108
P6SMB220A	220A	220C	209	231	1.0	185	1.0	1.9	328	0.108
P6SMB250A	250A	250C	237	263	1.0	214	1.0	1.8	344	0.108
P6SMB300A	300A	300C	285	315	1.0	256	1.0	1.5	414	0.108
P6SMB350A	350A	350C	332	368	1.0	300	1.0	1.3	482	0.108
P6SMB400A	400A	400C	380	420	1.0	342	1.0	1.1	548	0.108
P6SMB440A	440A	440C	418	462	1.0	376	1.0	1	602	0.108



Electrical Characteristics (Ta=25°C unless otherwise noted)

Device	Device Marking Code		Breakdown Voltage(Note 1) V _{BR} (V)		Test Current @I _T (mA)	Stand-Off Voltage V _{WM} (V)	Maximum Reverse Leakage at V _{WM} I _D (uA)	Maximum Peak Pulse Current I _{PPM} (Note 2) (A)	Maximum Clamping Voltage at I _{PPM} V _C (V)	Maximum Temperature Coefficient of V _{BR} (%/°C)
	Uni	Bi	Min	Max						
P6SMB480A	480A	480C	456.0	504.0	1.0	408	1.0	0.9	658.0	0.108
P6SMB510A	510A	510C	485.0	535.0	1.0	434	1.0	0.9	698.0	0.108
P6SMB530A	530A	530C	503.5	556.5	1.0	477.0	1.0	0.8	725.0	0.108
P6SMB540A	540A	540C	513.0	567.0	1.0	459.0	1.0	0.8	740.0	0.108
P6SMB550A	550A	550C	522.5	577.5	1.0	495.0	1.0	0.8	760.0	0.108

Notes 1. V_{BR} measured after I_T applied for 300us, I_T=square wave pulse or equivalent.

2. Surge current waveform per Fig. 3 and derate per Fig. 2.

3. For bipolar types having V_{WM} of 10 volts and under, the I_D limit is doubled

4. All terms and symbols are consistent with ANSI/IEEE C62.35.

Ratings and Characteristics Curves (Ta=25°C unless otherwise noted)

Fig.1 Peak Pulse Power Rating Curve




Fig. 2 Pulse Derating Curve




Fig.3 Pulse Waveform





Fig. 4 Typical Transient Thermal Impedance



Ratings and Characteristics Curves (Ta=25°C unless otherwise noted)

Fig. 5 Maximum Non-Repetitive Forward Surge Current Unidirectional Only




Fig. 6. Typical Junction Capacitance Unidirectional

