



Fast Recovery Rectifiers
Reverse Voltage 50 to 1000 Volts Forward Current 1.0 Ampere
Features

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability

Mechanical Data

- Case : Molded plastic
- Epoxy : UL 94V-0 rate flame retardant
- Lead : Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
- Polarity : Color band denotes cathode end
- High temperature soldering guaranteed : 260°C/10 seconds/0.375"(9.5mm) lead lengths at 5 lbs.,(2.3kg) tension
- Weight : 0.02 gram

Marking

Maximum Ratings & Electrical Characteristics (If not specified Ta =25°C)

Parameter	Symbol	F1T1	F1T2	F1T3	F1T4	F1T5	F1T6	F1T7	Unit	Remark
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V	
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V	
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V	
Maximum Average Forward Rectified Current 0.375"(9.5mm) Lead Length	$I_{(AV)}$	1.0							A	
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	30							A	
Maximum Instantaneous Forward Voltage @ 1.0A	V_F	1.2							V	
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	5.0							uA	Ta=25°C
		100.0								Ta=100°C
Maximum Reverse Recovery Time	t_{rr}	150			250	500		ns	Note 1	
Typical Junction Capacitance	C_J	15.0							pF	Note 2
Typical Thermal Resistance	$R_{th(j-a)}$	100							°C /W	Note 3
Operation Junction Temperature Range	T_J	-55 to +150							°C	
Storage Temperature Range	T_{STG}	-55 to +150							°C	

Note 1. Reverse Recovery Time Test Conditions : $I_F=0.5A$, $I_R=1.0A$, $I_{RR}=0.25A$

Note 2. Measured at 1MHz and Applied Reverse Voltage of 4.0Volts D.C.

Note 3. Mount on Cu-Pad Size 5mm × 5mm on P.C.B

Ratings and Characteristics Curves (Ta=25°C unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance





Fig. 5 Reverse Recovery Time Characteristic and Test Circuit Diagram



- NOTES: 1. Rise Time=7ns max. Input Impedance= 1 megohm 22pf
2. Rise Time=10ns max. Source Impedance= 50 ohms

