



## Silicon Rectifier

**Reverse Voltage 50 to 1000 Volts Forward Current 1.0 Ampere**



### Features

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability
- Ø 0.6mm Leads

### Mechanical Data

- Case : Molded plastic
- Epoxy : UL 94V-0 rate flame retardant
- Lead : Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- Polarity : Color band denotes cathode end
- High temperature soldering guaranteed : 260°C/10 seconds /0.375",(9.5mm) lead lengths at 5lbs.,(2.3kg) tension
- Weight : 0.22gram

### Marking



### Maximum Ratings & Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified

Single phase half wave 60 HZ, resistive or inductive load

For capacitive load, derate current by 20%

Parameter	Symbol	1N 4001S	1N 4002S	1N 4003S	1N 4004S	1N 4005S	1N 4006S	1N 4007S	Unit	Remark
Maximum Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V	
Maximum RMS Voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V	
Maximum DC Blocking Voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V	
Maximum Average Forward Rectified Current 0.375" (9.5mm)Lead Length	I <sub>F(AV)</sub>	1.0							A	
Peak Forward Surge Current 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	I <sub>FSM</sub>	30							A	
Maximum Instantaneous Forward Voltage @ 1.0A	V <sub>F</sub>	1.0							V	
Maximum DC Reverse Current at Rated DC Blocking Voltage	I <sub>R</sub>	5.0							uA	Ta=25°C
		50							uA	Ta=100°C
Maximum Full Load Reverse Current, Full Cycle Average 0.375"(9.5mm) Lead Length	H <sub>TIR</sub>	30							uA	Ta=75°C
Typical Junction Capacitance	C <sub>J</sub>	15							pF	Note 1
Typical Thermal Resistance	R <sub>th(j-a)</sub>	50							°C /W	Note 2
Operation Junction Temperature Range	T <sub>J</sub>	-55 to +150							°C	
Storage Temperature Range	T <sub>STG</sub>	-55 to +150							°C	

Note 1. Measured at 1MHz and Applied Reverse Voltage of 4.0Volts D.C.

Note 2. Mount on Cu-Pad Size 5mm×5mm on P.C.B.



Ratings and Characteristics Curves (Ta=25°C unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.3 Typical Instantaneous Forward Characteristics




Fig.5 Typical Reverse Characteristics




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.4 Typical Junction Capacitance

